



**SPECIFICATIONS**

**ELECTRICAL CHARACTERISTICS:**

Contact Current Rating: 3 Amperes.  
 Dielectric Withstanding Voltage: AC 1000V/60sec. r.m.s.  
 Insulation Resistance: 5000 Megohms Minimum. at DC 500.  
 Contact Resistance: 25 Milliohms Maximum.  
 Operating Temperature: -55°C to +105°C.

**MATERIALS:**

Contacts: Brass.  
 Insulator: PBT UL 94V-0 Rated.  
 Shell: Cold Roller Steel.

**FINISHES:**

Contact: Gold Flash.  
 Shell: Nickel Plated.

**MECHANICAL CHARACTERISTICS:**

D-SUB:  
 Insertion Force Per Contact: 341g. Maximum.  
 Separation Force Per Contact: 21g. Minimum.  
 MINI DIN:  
 Mating /Unmating Force: 1.0 kg. Minimum.  
 2.0 kg. Maximum.

**MORETHANALL**  
 CONNECTORS  
 ASSEMBLIES

焜倫有限公司

PART NO.	HDMD-FR-1566
DWG NO.	HDMD-FR-1566
FILE NO.	DM20B1C01002
UNIT / mm	SCALE 1:1

CHECKED BY	CY
DRAWING BY	
PROJECTION	

TOLERANCES ARE
.X
.XX ± 0.25
.XXX ± 0.13
AWG

DESCRIPTION:	D-SUB 15 FEMALE HIGH DENSITY /MINIATURE JACK x2			
	AREA	REVISIONS	HK	DATE