



RECOMMENDED P.C.B. LAYOUT

SPECIFICATIONS

ELECTRICAL CHARACTERISTICS:

Contact Current Rating: 3 Amperes.
 Dielectric Withstanding Voltage: AC 1000V/60sec. r.m.s.
 Insulation Resistance: 5000 Megohms Minimum. at DC 500.
 Contact Resistance: 25 Milliohms Maximum.
 Operating Temperature: -55°C to +105°C.

MECHANICAL CHARACTERISTICS:

Insertion Force Per Contact: 3 kg. Maximum.
 Separation Force Per Contact: 1 g. Maximum.

MATERIALS:

Contacts: Brass
 Insulator: PBT UL 94V-0 Rated.

FINISHES:

Contact: Gold Flash.
 Shell: Nickel Plated.



PART NO. HDMD-FR39-1566

DWG NO. HDMD-FR39-1566

APPROVED BY CY

TOLERANCES ARE

DESCRIP TION:

D-SUB 15 FEMALE HIGH DENSITY /MINIATURE JACK x2

煜倫有限公司

FILE NO.

DRAWING BY

.X ±0.25
.XX ±0.130
.XXX ±0.130
AWG

AREA

REVISIONS

HK

DATE

UNIT / mm

SCALE 1:1

PROJECTION

