

NOTES:

- 1:Material:  
 1.1 Housing: Thermoplastic UL94V-0 color:black.  
 1.2 Contact:Phosphor bronze T=0.30mm.  
 1.3 Shell:Copper alloy T=0.4mm.  
 1.4 Spacer: Thermoplastic UL94V-0 color:black.
- 2:Specification:  
 2.1 Current rating: 0.5 A Max.  
 2.2 Voltage rating: 4D V AC(rms) Max.  
 2.3 Contact resistance: 50 mW Max.  
 2.4 Dielectric withstanding  
 voltage: 100 V(ac) for 1 min.  
 2.5 Insulation resistance:1000 MW Min.  
 2.6 Operation temperature range:-25°C~85°C


RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
 PCB CONNECTORS  
 Cable ASSEMBLIES  
**煜倫股份有限公司**

DRAWING BY CY  
 CHECKED BY GENIUS  
 UNIT / mm SCALE 1 : 1  
 DATE  
 SIZE A4 PPROJECTION

X. ±  
 X ±  
 .XX ±  
 .XXX ±  
 ANG ±



ORDER INFORMATION

HDMI-PM-19-LF  
 SERIES | LEADFREE  
 | 19 WAY  
 | MOLDING  
 MALE

DESCRIPTION: HDMI-19P 夾板

www.morethanall.com