



RECOMMENDED PCB LAYOUT THICKNESS=1.6mm

TOLERANCE:±0.05

NOTE:

- 1.MATERIALS AND FINISHED
INSULATOR : LCP UL-94V0,
COVER:LCP UL-94V0
SHELL : BRASS, NICKEL PLATED
CONTACT MATERIAL : BRASS, SELEVITE GOLD FINISHED
- 2.ELECTRICAL CHARACTERISTICS
CONTACT CURRENT RATING : 0.5 AMPS
CONTACT VOLTAGE RATING:40VAC
CONTACT RESISTANCE :20 MILLIOHMS MAX.
DIELECTRIC WITHSTANDING VOLTAGE : 500 V AC MIN.
INSULATION RESISTANCE : 100 MEGAOHMS MIN.
- 3.MECHANICAL
MATING FORCE:4.5Kgf MAX.
UNMATING FORCE:1.0 Kgf MIN
- 4.ENVIRONMENTAL
TEMPERATURE RATING : -40°C ~ +100°C

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PJECTION

Up to 5 ±0.2
Above 5 ~ 15 ±0.3
Above 15 ~ 30 ±0.4
Above 30 ~ 50 ±0.5
Angle ±0.3°

照片框

ORDER INFORMATION

HDMI-SVM3H10C-19-LF

SERIES | | | | LEADFREE
FEMALE | | | | 19WAY
| | | | CAP
| | | | HIGH 10.5mm
| | | | METAL FOOT
| | | | 180°SMT

DESCRIPTION: HDMI AF 直立式 SMT TYPE

煜倫股份有限公司

www.morethanall.com