


CABLE SPECIFICATION

PIN ASSIGNMENT:

HDMI 19M		HDMI 19M
3	紅	3 (TMDS Data 2-)
1	白	1 (TMDS Data 2+)
2	地線	2 (TMDS Data 2 Shield)
6	綠	6 (TMDS Data 1-)
4	白	4 (TMDS Data 1+)
5	地線	5 (TMDS Data 1 Shield)
9	藍	9 (TMDS Data 0-)
7	白	7 (TMDS Data 0+)
8	地線	8 (TMDS Data 0 Shield)
12	棕	12 (TMDS Clock -)
10	白	10 (TMDS Clock +)
11	地線	11 (TMDS Clock Shield)
18	紅	18 (+5V Power)
17	白	17 (Ground)
15	黃	15 (SCL)
16	橙	16 (SDA)
19	灰	19 (Hot Plug Detect)
13	粉紅	13 (CEC)
14	紫	14 (RESERVED)
SHELL	編織	SHELL

ELECTRICAL CHARACTER:

1. 100% OPEN&SHORT TESTING
2. WITHSTANDING VOLTAGE:DC 300V 0.1Sec
3. INSULATION RESISTANCE:20M Ohms(Min)
4. CONDUCTIVE RESISTANCE:2 Ohms(Max)



5	COPPER FOIL	2PCS	CCB261001*	COPPER FOIL TO BE SOLDER AROUND 360°
4	OVERMOLD	14g	A0P70301*	PVC 70Pa BLACK UL94V-0
3	INNERMOLD	9g	A0005G01*	PE LOW DENSITY
2	HDMI CONN.	2	51S019P-32N4-E1*	HDMI 19P/M 端子鍍金G/F, 絕緣體黑色, 銅殼鍍銀.
1	HDMI CABLE	1500mm	ECB0630107302*	UL20276 (28AWG*1PR+DRAIN WIRE+FREE EDGE AL/MYLAR)*4 +28AWG*1P+28AWG*5C+AL+16/9/0.10T OD: Ø7.3±0.1mm C:BLACK IMPEDANCE:100 Ohms
序號 NO.	部品名稱 DESCRIPTION	用量 QTY.	料號 PART NO.	材質 MATERIAL

HDMIX2-191928-M3M-LF
LEADFREE

RoHS Compliant



PART NO. HDMIX2-191928-M3M

DWG NO. HDMIX2-191928-M3M

FILE NO.

CHECKED BY CY

DRAWING BY

PROJECTION

TOLERANCES ARE
.X ± 0.2
.XX ±
.XXX ±
AWG

DESCRIPTION:

HDMI 19P M*2			
AREA	REVISIONS	HK	DATE

煜倫股份有限公司

UNIT / mm

SCALE 1:1