



MATERIAL:

INSULATOR : PBT, UL 94V-0. Δ

CONTACT : COPPER ALLOY.

CONTACT FINISH : GOLD ON MATING END, TIN ON TERMINATION END,
WITH ENTIRE CONTACT NICKEL UNDERPLATED.

SHELL : STEEL.

BOARDLOCK : BRASS, TIN PLATED.

RIVETED INSERT : BRASS, NICKEL PLATED.

SPECIFICATION:

CURRENT RATING : 2 AMP

DIELECTRIC WITHSTANDING VOLTAGE : 1000V AC FOR 1 MINUTE.

INSULATION RESISTANCE : 1000M Ω MIN. AT 500V DC.

CONTACT RESISTANCE : 15m Ω MAX.

OPERATING TEMPERATURE : -55°C ~ +105°C.

HDR-PSN-78-LF
LEADFREE

RoHS Compliant



PART NO. HDR-PSN-78

DWG NO. HDR-PSN-78

FILE NO.

UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION

TOLERANCES ARE

.X \pm 0.2
.XX \pm 0.1
.XXX \pm
AWG

DESCRIPTION:

AREA

REVISIONS

HK

DATE

煜倫股份有限公司