



POS.	A	B	C	D	E
15	30.80	25.00	16.90	12.50	8.3
26	39.20	33.30	25.25	12.50	8.3
44	53.05	47.05	38.95	12.50	8.3
62	69.40	63.50	55.40	12.50	8.3

**MATERIALS AND FINISH**

**SHELL:** STEEL MATERIAL, FRONT SHELL NICKEL FINISHED  
 BACK SHELL NICKEL FINISHED  
 DIMPLES ON PLUG ONLY

**INSULATOR:** PBT THERMOPLASTIC, 30% GLASS FILLED,  
 UL 94V-0 RATED, BLACK COLOR

**CONTACT:** PRECISION MACHINED COPPER ALLOY  
 GOLD PLATED

**ELECTRICAL CHARACTERISTICS**

CONTACT CURRENT RATING : 3.0 A  
 CONTACT RESISTANCE : 10 mΩ MAX.  
 DIELECTRIC WITHSTANDING VOLTAGE : 1000 V AC MIN.  
 INSULATION RESISTANCE : 5GΩ MIN.  
 TEMPERATURE RATING : -55°C ~ +125°C

**RoHS Compliant**

TOLERANCES ARE



**煜倫股份有限公司**

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X. ± 0.40

.X ± 0.30

.XX ± 0.20

.XXX ± 0.10

ANG ± 5°

P PROJECTION

照片框

**ORDER INFORMATION**

HDSM-P-xx-LF

SERIES | LEADFREE

15-62WAY

MALE

DESCRIPTION: