



pin out:

| | | | |
|----|---------------------|----|---------------------------|
| P1 | | P1 | |
| 1 | 28# grey tin | 13 | 28# grey/black ring tin |
| 2 | 20# red tin | 14 | 28# red/black ring tin |
| 3 | | 15 | 28# orange/black ring tin |
| 4 | | 16 | 28# white/black ring tin |
| 5 | 28# purple tin | 17 | 28# yellow/black ring tin |
| 6 | 28# purple tin | 18 | 28# green/black ring tin |
| 7 | 28# white tin | 19 | 28# purple/black ring tin |
| 8 | 28# blue tin | 20 | 28# blue/black ring tin |
| 9 | 28# yellow tin | 22 | 28# brown tin |
| 10 | 20# black+drain tin | 23 | 28# pink tin |
| 11 | | 24 | 28# green tin |
| 12 | | 26 | 28# azury tin |
| | shell | | braid tin |

| ITEM | DESCRIPTION | QTY |
|------|---|-----|
| 1 | HD D-SUB 26P MALE SOLDER TYPE | 1 |
| 2 | NO UL 20AWG*2C+28AWG*18C+AEB OD:6.5MM COLOR BLACK PU JACKET | |
| 3 | #4-40UNC L=45MM SCREW | 2 |
| 4 | PVC MODING 50P COLOR BLACK | |
| 5 | H.S TUBE OD:0.8 COLOR BLACK | |

HDX1-2600-M1M94-LF
LEADFREE
RoHS Compliant



PART NO. HDX1-2600-M1M94

DWG NO. HDX1-2600-M1M94

CHECKED BY CY

TOLERANCES ARE

DESCRIP TION:

FILE NO.

DRAWING BY

.X ± 0.2
.XX ±
.XXX ±
AWG

AREA

REVISIONS

HK

DATE

煜倫股份有限公司

UNIT / mm

SCALE 1:1

PROJECTION

