



pin out:

P1	1	28# grey	tin	P1	13	28# grey/black ring	tin
	2	20# red	tin		14	28# red/black ring	tin
	3				15	28# orange/black ring	tin
	4				16	28# white/black ring	tin
	5	28# purple	tin		17	28# yellow/black ring	tin
	6	28# purple	tin		18	28# green/black ring	tin
	7	28# white	tin		19	28# purple/black ring	tin
	8	28# blue	tin		20	28# blue/black ring	tin
	9	28# yellow	tin		22	28# brown	tin
	10				23	28# pink	tin
	11	20# black+drain	tin		24	28# green	tin
	12					26	28# azury
				shell		braid	tin

ITEM	DESCRIPTION	QTY
1	HD D-SUB 26P MALE SOLDER TYPE	1
2	NO UL 20AWG*2C+28AWG*18C+AEB OD:6.5MM COLOR BLACK PU JACKET	
3	#4-40UNC L=45MM SCREW	2
4	PVC MODING 50P COLOR BLACK	
5	H.S TUBE OD:0.8 COLOR BLACK	

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±
.X ± 0.30
.XX ± 0.20
.XXX ± 0.10
ANG ±

PPOJECTION

照片框

ORDER INFORMATION

HDX1-26002028-M1M94-LF

SERIES

26 WAY

MALE
20/28 AWG

1940mm

LEADFREE

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: