



MATERIAL:

INSULATOR : PBT+30% GLASS FIBER (UL 94V-0) 661C BLUE.
 CONTACT MATERIAL : BRASS.
 CONTACT FINISH : GOLD FLASH ON MATING END, TIN-LEAD ON TERMINATION END, WITH ENTIRE CONTACT NICKEL UNDERPLATED.
 SHELL FINISH : STEEL, NICKEL PLATED.

SPECIFICATION:

CURRENT RATING : 2 AMP
 DIELECTRIC WITHSTANDING VOLTAGE : 1000V PER MINUTE
 INSULATION RESISTANCE : 1000MΩ MIN. AT 500V DC.
 CONTACT RESISTANCE : 25mΩ MAX. 10 SEC.
 OPERATING TEMPERATURE : -55°C ~ +105°C.

MORE THAN ALL
 CONNECTORS
 ASSEMBLIES

PART NO. HDXX-FR-1500

DWG NO. HDXX-FR-1500

APPROVED BY CY

TOLERANCES ARE

DESCRIP TION: HIGH DENSITY D-SUB HIGH RISE 15S 661C BLUE

煜倫有限公司

FILE NO. 01AH-150S1BJBN

DRAWING BY

X ± 0.25
 .XX ± 0.15
 .XXX ± 0.05
 AWG

UNIT / mm

SCALE 1:1

PROJECTION

| | | | |
|------|-----------|----|------|
| AREA | REVISIONS | HK | DATE |
|------|-----------|----|------|