



接點示意圖

P1	P2
1	1
2	2
3	3
4	4
5	5
6	6
.	.
.	.
.	.
87	87
88	88
89	89
90	90
91	91
92	92
93	93
94	94
95	95
96	96
97	97
98	98
99	99
100	100

⑤	紙箱	PCS	40*34*30CM
④	防水袋	PCS	88*88CM
③	PE袋	1/25PCS	21*25CM
②	插頭	2PCS	IDC 100P PH:1.27*2.54MM 黑色有耳三件
①	線材	1PCS	UL20276 30AWG 50PR(1P:RED/WHITE,49P:BLUE/WHITE)藍白芯線 L=660MM
NO.	NAME	Q'TY	DESCRIPTION

ELECTRICAL CHARACTER:
 1. 100% OPEN/SHORT.
 2. CONTACT RESISTANCE: 20HMS
 3. HI-POT: 300V 10MS
 4. INSULATION RESISTANCE: 20MOHMS

	PART NO. HF3X2-A0A0-F60C		TOLERANCES ARE .X ± 0.2 .XX ± .XXX ± AWG	DESCRIP TION:				
	DWG NO. HF3X2-A0A0-F60C							CHECKED BY CY
煜倫有限公司	FILE NO.		DRAWING BY		AREA	REVISIONS	HK	DATE
	UNIT / mm	SCALE 1:1	PROJECTION					