



PCB LAYOUT

MATERIAL:

Contact:

phosphor Bronze thickness 0.17mm

Contact Plating: Sn-Cu plated 120u"~200u"

Insulator: PBT-4830 , UL 94V-0

SPECIFICATIONS:

Current Rating : 1A

Dielectric withstanding Voltage : 1000v RMS/minute

Insulator resistance : 5000 Megohms min.

Contact resistance : 20 milliohms initial

30 milliohms after test.

Operating temperatures : -55°c to 85°c

Insertion force : 340g (12 oz) max.per contact.

Withdrawal force : 80g (2.82 oz) min.per contact

PART NO	CKT	A±0.20	B±0.20	C±0.20	D±0.20
HIC-D07-64	64	56.90	55.12	21.55	19.05

RoHS Compliant

TOLERANCES ARE



煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X.±
.X±
.XX±
.XXX±
ANG±

PJECTION

照片框

ORDER INFORMATION

HIC-D07-64-LF
SERIES | LEADFREE
64 WAY
SPACING 19.05mm
DIP 180°

DESCRIPTION: