

FEATURES:






- Half pitch 1.27mm(.050") series
- Centronic male connector I.D.C type for cable
- Assembly hood: plastic(steel inner shell)
- Fully EMI/RFI shielded

MATERIALS:


- Housing And Cover: Plastic thermoplastic
P.B.T UL94V-0 black
- Contacts: Phosphor bronze gold
selective plated
- Shell: Steel nickel plated over copper

ELECTRICAL:






- Current Rating: 1 Amp
- Insulation Resistance: 500MΩ/Min
- Withstanding Voltage: 500V AC/Min
- Contact Resistance: 35mΩ Max
- Temperature Range: -55°C ~ +105°C



Termination Cover
(1 Places)



Wire Holder
(2 Places)



RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY
CHECKED BY GENIUS
UNIT / mm SCALE 1 : 1
DATE

X. ±
.X ±
.XX ±
.XXX ±
ANG ±

照片框

ORDER INFORMATION

HPC-PF-020-LF
SERIES | LEADFREE
20 WAY
IDC
MALE

煜倫股份有限公司

www.morethanall.com

SIZE A4 PPROJECTION

DESCRIPTION: 1.27mm(.050") Pitch Centronic 20P Male Connector I.D.C Assembly Type