



PCB Layout

- Housing And Cover: Plastic Thermoplastic P.B.T UL94V-0 Black
 Contacts: Phosphor Bronze Gold Selective Plated
 Front Shell: Steel Nickel Plated Over Copper
 Bracket: Steel Nickel Plated Over Copper
 Boardlock: Brass Tin Plated Over Copper

- ELECTRICAL CHARACTERISTICS:

Contact Current Rating: 0.5 Amp
 Dielectric Withstanding Voltage: 500V AC
 Insulation Resistance: >500MΩ/Min
 Contact Resistance: 35mΩ/Max
 Operation Temperature: -55°C ~ +85°C

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

DATE _____

SIZE A4

SCALE 1 : 1

PROJECT

X. $\pm$
.X $\pm$
.XX $\pm$
.XXX $\pm$
ANG $\pm$

ON 

照片框

ORDER INFORMATION

HPC-SRX-100-LF
 SERIES 100 WAY LEADFREE
 NON LOCK
 DIP 90°
 FEMALE

DESCRIPTION: 1.27mm (.050") Ribbon 100Pos Receptacles Headers Right-Angle Mount Type