



P1		P2		P1		P3	
HPC	DB	HPC	DB	HPC	DB	HPC	DB
50PIN (M)	25PIN (F)	50PIN (M)	25PIN (F)	50PIN (M)	25PIN (F)	50PIN (M)	25PIN (F)
28	4	21	4	21	4	21	4
10	5	22	5	22	5	22	5
25	7	26	7	26	7	26	7
43	8	39	8	39	8	39	8
15	9	1	9	1	9	1	9
2	10	14	10	14	10	14	10
46	11	8	11	8	11	8	11
45	12	9	12	9	12	9	12
16	13	4	13	4	13	4	13
3	14	17	14	17	14	17	14
32	19	7	19	7	19	7	19
19	21	20	21	20	21	20	21
13	20	27	20	27	20	27	20
SHELL	SHELL	SHELL	SHELL	SHELL	SHELL	SHELL	SHELL

RoHS

- 100% OPEN / SHORT / INSULATING TEST
- INSULATION TEST: 2MΩ

COMPONENTS	DESCRIPTION	Q'TY
1 HPC 50M	Half Pitch 1.27mm 50P Male Connector Shell: Steel Nickel Plated Insulator: Black P.B.T Contact: Phosphor Bronze 15μ" Gold Plating	1
2 Jackscrew	UNC M2.6 Metal Nickel Plated	2
3 Hood	Zinc Alloy Die-Cast Nickel Plated	1
4 Cable	UL2990 28AWG 8P A+E+B Color: Beige	2
5 DB25F	D-SUB 25P Female Connector Shell: Steel Nickel Plated Insulator: Black P.B.T Contact: Brass G/F Gold Plated	2
6 Jackscrew	UNC #4-40 Nickel Plated Hood: ABS Color: Beige	4
7 Hood	P.V.C Molded Color: Beige	2

HPCDBX12-5025-E8N-LF
LEADFREE
RoHS Compliant

	PART NO. HPCDBX12-5025-E8N		TOLERANCES ARE .X ± 0.2 .XX ± .XXX ± AWG	DESCRIPTION:	AREA	REVISIONS	HK	DATE
	DWG NO. HPCDBX12-5025-E8N							
	FILE NO.		DRAWING BY					
	UNIT / mm	SCALE 1:1	PROJECTION					