



MATERIAL :
 INSULATOR : PBT+30% GLASS FIBER (UL94V-0)
 CONTACT : PHOSPHOR BRONZE OR BRASS
 CONTACT PLATED : GOLD OR TIN OVER NICKEL

SPECIFICATION :
 CURRENT RATING : 1AMP.
 WITHSTANDING VOLTAGE : AC 500V R.M.S
 INSULATION RESISTANCE : 1000MEGOHMS MINIMUM
 AT DC 500V.
 CONTACT RESISTANCE : 15 MILLIOHMS MAXIMUM.
 OPERATING TEMPERATURE ; -40°C~105°C.

PIN	A	B	C	
20	24.15	19.73	11.43	
40	36.85	32.43	24.13	
50	43.2	38.78	30.48	
68	54.63	50.21	41.91	
80	62.25	57.83	49.53	

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X, ±
 .X ± 0.20
 .XX ± 0.10
 .XXX ± 0.05
 ANG ± 1°

PPOJECTION

照片框

ORDER INFORMATION

HPCP-PD2-xxx-LF

SERIES
 LEADFREE
 020~080 WAY
 TWO ROW
 DIP 180°
 FEMALE

DESCRIPTION: