



MATERIAL:

- 1.HOUSING: PBT+30 %G.F.(UL 94V-0)
- 2.TERMINAL: Phosphor Bronze,C5191R-H T=0.3±0.01mm
- 3.TERMINAL PLATED: GOLD FLASH ON CONTACT;
100μ" MIN NICKEL OVERALL.

SPECIFICATION:

- 1.CURRENT RATING:0.5 AMP. MAX.
- 2.DIELECTRIC WITHSTANDING VOLTAGE:500V AC
R.M.S. FOR ONE MINUTE.
- 3.INSULATION RESISTANCE:1000M OHMS MIN.
- 4.CONTACT RESISTANCE :30m OHMS MAX.
- 5.OPERATING TEMPERATURE :-20°C TO +85°C.

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1:1

DATE

SIZE A4

X. ±

.X ±

.XX ±

.XXX ±

ANG ±

PJECTION

照片框

ORDER INFORMATION

HPCP-SF2-080-LF

SERIES | | LEADFREE
| | 080 WAY
| | TWO TYPE
IDC
FEMALE

DESCRIPTION: 刺破式(ASS'Y) CUSTOMER