



Length Unit:CM	Tolerance
< 50	± 2
50-100	± 3
101-150	± 4
151-300	± 5
301-500	± 6
> 500	± 10

Length Unit:CM

- RoHS**
- 100% OPEN / SHORT / INSULATING TEST
 - INSULATION TEST: 2MΩ

COMPONENTS	DESCRIPTION	Q'TY
1	HPC-100M Half Pitch 1.27mm 100P Male Connector. Shell: Steel Nickel Plated Insulator: Black P.B.T. Contact: Copper Alloy 5μ" Gold Plated	2
2	Hood Zinc Alloy Die-Cast Nickel Plated	2
3	Jack screws M2.6 Metal Nickel Plated	4
4	Cable (D5499D) UL2990 28#50P A+E+B Impedances: 90Ω ±15Ω OD:10.4mm Color: Black	1
5	SR P.V.C Molded Color: Black	2



煜倫股份有限公司

www.morethanall.com

RoHS Compliant

DRAWING BY CY
CHECKED BY GENIUS
UNIT / mm SCALE 1:1
DATE
SIZE A4

TOLERANCES ARE

X. ±
.X ±
.XX ±
.XXX ±
ANG ±



照片框

ORDER INFORMATION

HPCX2-10010028M1-M1M2-LF
SERIES | | | | LEADFREE
| | | | 1200mm
| | | | MALE TO MALE
| | | | METAL
| | | | 28 AWG
| | | | 100 TO 100 WAY

DESCRIPTION: