



- 100% OPEN / SHORT / INSULATING TEST
- INSULATION TEST: 2MΩ

COMPONENTS:	DESCRIPTION	Q'TY
1 Jackscrew	M2.6 Metal Nickel Plated	4
2 HPC-PSM-040	Half Pitch Centronic 1.27mm 40P Male Connector Shell: Steel Nickel Plated Insulator: Black P.B.T Contact: Copper alloy 5 μ Gold Plated.	2
3 Hood	Zinc Alloy Die-Cast Nickel Plated	2
4 Cable	UL2990 28AWG 25Pairs OD: 8.5mm AEB Impedance: 90 Ω ±10 Ω Color: Black L: XXXXmm	1

Length Unit:CM	Tolerance
< 50	± 2
51-100	± 3
101-150	± 4
151-300	± 5
301-500	± 6
> 500	± 10

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X. ±
.X ±
.XX ±
.XXX ±
ANG ±

PJECTION

照片框

ORDER INFORMATION

HPCX2-404028M1-Mxxx-LF

SERIES

40 TO 40 WAY

METAL
28 AWG

LEADFREE
1M:1000mm
1M2:1200mm
MALE TO MALE

DESCRIPTION: