



- 100% OPEN / SHORT / INSULATING TEST
- INSULATION TEST: 2MΩ

| COMPONENTS   | DESCRIPTION  | Q'TY |
|--------------|--|------|
| 1 FMC68M     | Half Pitch Centronic 1.27mm 68P Male Connector. Shell: Steel Nickel Plated<br>Insulator: Black P.B.T. Contact: Phosphor Bronze 5μ" Gold Plated | 2    |
| 2 Hood       | Zinc Alloy Die-Cast Nickel Plated  | 2    |
| 3 Jackscrews | M2#56 Metal Nickel Plated  | 4    |
| 4 Cable      | UL2990 28AWG 34P AEB Impedance 90Ω ±10Ω<br>Color: Black L: XXXXmm  | 1    |
| 5 SR         | P.V.C Molded Color: Black  | 2    |

| Length Unit:CM | Tolerance |
|----------------|-----------|
| < 50           | ± 2       |
| 50-100         | ± 3       |
| 101-150        | ± 4       |
| 151-300        | ± 5       |
| 301-500        | ± 6       |
| > 500          | ± 10      |



煜倫股份有限公司

www.morethanall.com

RoHS Compliant

DRAWING BY CY  
CHECKED BY GENIUS  
UNIT / mm SCALE 1 : 1  
DATE  
SIZE A4

TOLERANCES ARE

X. ±  
.X ±  
.XX ±  
.XXX ±  
ANG ±



照片框

ORDER INFORMATION

HPCX2-686828M1-Mxxx-LF  
SERIES  
68 TO 68 WAY  
LEADFREE  
1M:1000mm  
1M2:1200mm  
MALE TO MALE  
METAL  
28 AWG

DESCRIPTION: