

FEATURES:

- Half pitch 1.27mm(.050") series
- D-SUB Male connector solder type for cable
- Assembly hood: with ABS plastic (steel inner shell) or Die-Cast metal
- Fully EMI/RFI shielded

MATERIALS:

- **Housing:** Thermoplastic P.B.T UL94V-0 black
- **Contacts:** Phosphor bronze mating end selective gold plated
- **Front Shell:** Steel nickel plated over copper

ELECTRICAL:

- **Current Rating:** 1 Amp
- **Insulation Resistance:** 500MΩ/Min
- **Withstanding Voltage:** AC 500V/Min
- **Contact Resistance:** 35mΩ MAX
- **Temperature Range:** -55°C ~ +105°C

MORETHANALL
CONNECTORS
ASSEMBLIES

焯倫有限公司

PART NO. **HPD-PS-050**

DWG NO. **HPD-PS-050**

FILE NO.


UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION



TOLERANCES ARE

.X±
.XX±
.XXX±
AWG

DESCRIPTION:

AREA

1.27mm(.050") Pitch D-SUB 50P

**Male Connector Solder
Assembly Type**

REVISIONS

HK

DATE