



### SPECIFICATIONS

#### ELECTRICAL CHARACTERISTICS:

Contact Current Rating: 1 Amperes.  
 Dielectric Withstanding Voltage: AC 500/60sec.r.m.s.  
 Insulation Resistance: 1000 Medohms Minimum  
 Contact Resistance: 35 Milliohms Maximum.  
 Operating Temperature: -55°C to +85°C.

#### MECHANICAL CHARACTERISTICS:

Contact Engagement Force: 141.8g. Maximum.  
 Contact Separation Force: 17g. Minimum.

#### MATERIALS:

Contacts: Brass.  
 Insulator: PBT UL 94V-0 Rated.  
 Bracket: Zinc Alloy, Grade 3  
 Metal Clip: Brass.

#### FINISHES:

Contact: Gold Flash.  
 Bracket: Nickel Plated

**MORETHANALL**  
 CONNECTORS  
 ASSEMBLIES

煜倫有限公司

PART NO.	HPDB1-SR-068	CHECKED BY	CY	TOLERANCES ARE	DESCRIPTION:	SCSI II PIN TYPE RIGHT ANGLE DUAL PORT			
DWG NO.	HPDB1-SR-068	DRAWING BY		.X ± .XX ± .XXX ± AWG					
FILE NO.		PROJECTION			AREA	REVISIONS	HK	DATE	
UNIT / mm	SCALE 1:1								