

Length Unit:CM	Tolerance
< 50	± 2
50-100	± 3
101-150	± 4
151-300	± 5
301-500	± 6
> 500	± 10

**RoHS**

- 100% OPEN / SHORT / INSULATING TEST
- INSULATION TEST: 2M Ω

COMPONENTS	DESCRIPTION	Q'TY
1 FMD100M	Half Pitch D-SUB 1.27mm 100P Male Connector. Shell: Steel Nickel Plated Insulator: Black P.B.T. Contact: Copper Alloy 5μ" Gold Plated	2
2 Hood	Zinc Alloy Die-Cast Nickel Plated	2
3 Jackscrews	UNC 2#56 Metal Nickel Plated	4
4 Cable	UL2990 28AWG 50Pair A+E+B Impedances: 90 Ω ±15 Ω OD:10.4mm Color: Beige	1
5 SR	P.V.C Molded Color: Beige	2

HPDX2-100100-MxxxC-LF  
LEADFREE  
200:200CM (2 METER)

RoHS Compliant



PART NO. HPDX2-100100-MxxxC

DWG NO. HPDX2-100100-MxxxC

FILE NO.


UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION



TOLERANCES ARE

- .X ± 0.2
- .XX ± 0.1
- .XXX ±
- AWG

DESCRIPTION:

AREA

REVISIONS

HK

DATE

煜倫股份有限公司