



Length Unit:CM	Tolerance
< 50	± 2
51-100	± 3
101-150	± 4
151-300	± 5
301-500	± 6
> 500	± 10

RoHS

- 100% OPEN / SHORT / INSULATING TEST
- INSULATION TEST: 2MΩ

COMPONENTS:	DESCRIPTION	Q'TY
1 Jackscrew	UNC #2-56 Metal Nickel Plated	4
2 FMD40M	Half Pitch D-SUB 1.27mm 40P Male Connector Shell: Steel Nickel Plated Insulator: Black P.B.T Contact: Copper alloy 5μ" Gold Plated.	2
3 Hood	Zinc Alloy Die-Cast Nickel Plated	2
4 Cable	UL2990 28AWG 25Pairs OD: 8.5mm AEB Impedance: 90Ω ±10Ω Color: Beige L: XXXXmm	1

HPDX2-4040-MxxxC-LF
LEADFREE
050:50CM
500:500CM

RoHS Compliant

	PART NO. HPDX2-4040-MxxxC		TOLERANCES ARE .X ± 0.2 .XX ± .XXX ± AWG	DESCRIPTION:	AREA	REVISIONS	HK	DATE
	DWG NO. HPDX2-4040-MxxxC							
焯倫股份有限公司	FILE NO.		DRAWING BY					
	UNIT / mm	SCALE 1:1	PROJECTION					