



- 100% OPEN / SHORT / INSULATING TEST
- INSULATION TEST: 2MΩ

COMPONENTS:	DESCRIPTION	Q'TY
1 Jackscrew	UNC #2-56 Metal Nickel Plated	4
2 FMD68M	Half Pitch D-SUB 1.27mm 68P Male Connector Shell: Steel Nickel Plated Insulator: Black P.B.T Contact: Phosphor bronze 5μ" Gold Plated.	2
3 Hood	Zinc Alloy Die-Cast Nickel Plated	2
4 Cable (7484R)	UL20276 30AWG 32Pairs 28AWG 2Pairs I.D:0.65mm O.D:9.8mm Impedance: 130Ω ±10Ω Color: Beige L: 1500mm	1
5 SR	PVC Molded Color: Beige	2

HPDX2-6868-M1M5-LF
LEADFREE

RoHS Compliant



PART NO. HPDX2-6868-M1M5

DWG NO. HPDX2-6868-M1M5

CHECKED BY CY

TOLERANCES ARE

FILE NO.

DRAWING BY

.X ± 0.2
.XX ± 0.1
.XXX ±

DESCRIPTION: SCSI Cable L : 150CM(1.5M)

煜倫股份有限公司

UNIT / mm

SCALE 1:1

PROJECTION

AWG

AREA	REVISIONS	HK	DATE