



RoHS

- 100% OPEN / SHORT / INSULATING TEST
- INSULATION TEST: 2MΩ

HPDX2-68A68A-M1M-LF
LEADFREE
RoHS Compliant

COMPONENTS:	DESCRIPTION	Q'TY
1 HPD-PFWA-068	Half Pitch D-SUB 1.27mm 68P Male Connector Shell: Steel Nickel Plated Insulator: Black P.B.T Contact: Phosphor bronze 5μ" Gold Plated.	2
2 Hood	Zinc Alloy Die-Cast Nickel Plated	2
3 USL/SF	Spring Latches Phosphor Bronze Nickel Plated	4
4 Cable (7484R)	UL20276 30AWG 32Pairs 28AWG 2Pairs I.D:0.65mm O.D:9.8mm Impedance: 130Ω ±10Ω Color: Black L: 1000mm	1

MORETHANALL
CONNECTORS
ASSEMBLIES

焯倫股份有限公司

PART NO. HPDX2-68A68A-M1M	CHECKED BY CY	TOLERANCES ARE	DESCRIP TION: SCSI Cable L : 100CM				
DWG NO. HPDX2-68A68A-M1M	DRAWING BY	.X ± 0.2 .XX ± .XXX ± AWG					
FILE NO.	UNIT / mm	SCALE 1:1	PROJECTION	AREA	REVISIONS	HK	DATE