



Recommended P.C.B Layout

### MATERIAL

Insulator : NY6T UL94-V0

Contact Pin : Brass

### SPECIFICATION

Current Rate : 3 AMP

Insulation Resistance : 5000MΩMin. at DC 500V

Contact Resistance : 20mΩMax. at DC 100mA

Dielectric Voltage : AC 500V for one minute

Operation Temperature : -40°C to + 105°C

**RoHS Compliant**

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

**煜倫股份有限公司**

[www.morethanall.com](http://www.morethanall.com)

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X, ±  
.X ± 0.30  
.XX ± 0.20  
.XXX ±  
ANG ± 3°

PJECTION

照片框

### ORDER INFORMATION

HS-D0943034-1X06E345-LF  
SERIES | | | | | | | |  
LEADFREE  
06 WAY EMPTY#3.4.5 PIN  
DIP 3.4mm  
CONTACT 3.0mm  
LONG 9.4mm  
180°SMT

DESCRIPTION: PIN HEADER 2.54\*2.54mm STRAIGHT TYPE, SINGLE ROW DUAL INSULATORS