



P. C. B . LAYOUT

MATERIAL

HOUSING : NY6T, UL-94V0
 CONTACT : COPPER ALLOYS
 PLATED : GOLD FLASH
 COLOR : BLACK

SPECIFICATION

CURRENT : 3A
 OPERATING TEMPERAURE : -55° C TO +105° C
 CONTACT RESISTANCE : 20 MILLIOHMS MAX
 INSULATION RESISTANCE: 1000 MEGAOHMS MIN
 WITHSTAND VOLTAGE : 1000 V AC/minute

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1:1

DATE

SIZE A4

X. ±
 .X ± 0.38
 .XX ± 0.25
 .XXX ±
 ANG ± 5°

PPOJECTION

照片框

ORDER INFORMATION

HS-D143607534-1X10C19-LF
 SERIES | LEADFREE
 10 WAY CONTACT 1~8:6.0mm&9~10:7.5mm
 DIP 3.4mm
 CONTACT 6.0/7.5mm
 TOTAL 14.3mm
 DIP 180°

DESCRIPTION: PH2.54 雙塑 180° H:1.70 1*10 PIN