



MATERIAL

Contact Pin : Brass
 Insulator: PBT UL94-V0

SPECIFICATION

Current Rate : 3 AMP
 Insulation Resistance : 5000MΩMin. at DC 500V
 Contact Resistance : 20mΩMax. at DC 100mA
 Dielectric Voltage : AC 500V for one minute
 Operation Temperature : -40°C to + 105°C

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4 PPROJECTION

X, ±
 .X ± 0.30
 .XX ± 0.20
 .XXX ±
 ANG ± 3°

照片框

ORDER INFORMATION

HS-RH60325869-2X07-LF
 SERIES | HIGH TYPE | CONTACT 3.2mm | R/A 6.0mm
 DIP 90° | HIGH TYPE | CONTACT 3.2mm | R/A 6.0mm
 LEADFREE | 14 WAY | HIGH 6.9mm | DIP 5.8mm

DESCRIPTION: PIN HEADER 2.54*2.54mm RIGHT ANGLE TYPE, DUAL ROWS DUAL INSULATORS