



Recommended P.C.B Layout

MATERIAL

Insulator : NY6T UL94-V0

Contact Pin : Brass

SPECIFICATION

Current Rate : 3 AMP

Insulation Resistance : 5000MΩMin. at DC 500V

Contact Resistance : 20mΩMax. at DC 100mA

Dielectric Voltage : AC 500V for one minute

Operation Temperature: -40°C to +105°C

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X. ±
.X ± 0.30
.XX ± 0.20
.XXX ±
ANG ± 3°

PPOJECTION

照片框

ORDER INFORMATION

HSB-D1386028-1X01-LF
SERIES | | | | LEADFREE
| | | | 01 WAY
| | | | DIP 2.8mm
| | | | CONTACT 6.0mm
| | | | TOTAL 13.8mm
| | | | DIP180°

DESCRIPTION: PIN HEADER 2.54*2.54mm STRAIGHT TYPE, SINGLE ROW OPPOSITE INSULATORS

煜倫股份有限公司

www.morethanall.com