



MATERIALS

- * Body : L.C.P. UL 94V-0
- * Contact : Bronze
- * Contact plating : Sn
- * Recommended industry standard modules (1.19mm[0.47in.] to 1.37mm[0.54in.] thick)

SPECIFICATIONS

- * Contact rating: 1Amp
- * Contact resistance: 30 Megohms Max.
- * Insulation resistance: 1000 Megohms at 500 DC
- * Dielectric strength: 1.27mm[0.05in.] pitch-1000VAC RMS, 2.54mm[0.10in.] pitch-1500VAC RMS
- * Capacitance: 1 pF Max.
- * Vibration: MIL-STD-1344A
- * Duridity: 30 Cycles
- * Insertion force: 0g
- * Withdrawal force: 0g
- * Contact (normal) force: 150g Min.
- * Contact retention force: 2 pounds per circuit Min.
- * Operating and storage temperature: -40°C to +100°C
- * Humidity: MIL-STD-202, Method 106D, 10 days
- * Temperature soak: 85°C for 160 hours
- * Thermal shock: 5 cycles, -40°C to +85°C per MIL-STD-202, Method 107E

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±
.X ±
.XX ±
.XXX ±
ANG ±

PJECTION

照片框

ORDER INFORMATION

HSM-D-1X72-LF
SERIES | LEADFREE
72 WAY
DIP 180°

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: SIMM SOCKET 1X72P Vertical