



* SPECIFICATION :

* ITEM :

UNIT : $\frac{\text{inch}}{\text{mm}}$

DL-						SQ PIN	FOR CRIMPING RG TYPE CABLE	
801A		.255" 6.48	.213" 5.41		.068" 1.72		58, 59, 62, 140, BELDEN 8279	
801B	.319" 8.1		.213" 5.41	.187" 4.75			58, 6, 174, 140, FIBER OPTIC	
801C	.319" 8.1	.256" 6.5	.213" 5.41		.068" 1.72		58, 59, 62, 6, BELDEN 8279	
801F	.350" 8.9	.320" 8.13	.255" 6.48				CATV F CONN. RG59, 6	
801F2	.213" 5.41	.178" 4.52	.151" 3.84		.068" 1.72	.042" 1.07	58, 174, BELDEN 8281 FIBER OPTIC SMA,SMB CONNECTORS	
801F5	.213" 5.41	.178" 4.52	.128" 3.25	.068" 1.72	.042" 1.07	.028" 0.71	58, 174, FIBER OPTIC F2 F3 F5	
801G	.255" 6.48	.213" 5.41	.137" 3.5	.100" 2.54	.068" 1.72	.043" 1.10	58, 59, 62, 174, 140, FIBER OPTIC	
801J	.178" 4.52	.151" 3.84	.128" 3.25	.078" 2.0	.068" 1.72	.042" 1.07	174, 178, 179, FIBER OPTIC	
801K	.429" 10.9		.128" 3.25	.100" 2.54	.075" 1.9		8, 9, 11, 174, 316, BELDEN 9913	
801V	.187" 4.75	.178" 4.52	.151" 3.84	.137" 3.5	.128" 3.25	.068" 1.72	.042" 1.07	58, 174, SMA SMB
830B	.324" 8.22	.255" 6.48			.068" 1.72		59, 62, 6, BELDEN 8281	
830C		.255" 6.48	.213" 5.41	.187" 4.75	.068" 1.72		58, 59, 62, 142, 174, 223	
830D			.213" 5.41	.187" 4.75	.151" 3.84	.128" 3.25	58, 174, FIBER OPTIC	

GENERAL SPECIFICATIONS:

- * LENGTH : 8-7/8" (225 ± 3 mm)
- * MT'L : 2.8 mm MIDDLE CARBON STEEL.
- * HARDNESS : HRC 42~48
- * FRAME : BLACK OXIDE FINISHED.

HT-RF-xxxx-LF
LEADFREE

RoHS Compliant

M MORETHANALL
CONNECTORS
ASSEMBLIES

煜倫股份有限公司

PART NO. HT-RF-xxxx		CHECKED BY CY		TOLERANCES ARE		DESCRIP TION: RATCHET CRIMPING TOOL		
DWG NO. HT-RF-xxxx		DRAWING BY		.X ± 0.2 .XX ± 0.1 .XXX ± AWG		AREA		
FILE NO.	UNIT / mm	SCALE 1:1	PROJECTION			REVISIONS	HK	DATE