

1. Housing:
 1.1 Material: PBT + glass fiber
 1.2 Color: black

2. Terminal:
 2.1 Material: Phosphorus copper
 2.2 Surface treatment/finish: Nickel plated (100u"min)
 2.3 Instant thrust: 0.5kg per pin

3. Electrical reference:
 3.1 Current rating: 1A
 3.2 Dielectric withstanding voltage: AC 1000V/5S
 3.3 Insulator resistance: 1000 Megohms 500V DC
 3.4 Operating temperature: -55°C ~ +105°C

PART NO.	A	B	SPACING
IC-D03-06	7.62	5.08	0.3
IC-D03-08	10.16	7.62	
IC-D03-14	17.78	15.24	
IC-D03-16	20.32	17.78	
IC-D03-18	22.86	20.32	
IC-D03-20	25.40	22.86	
IC-D03-22	27.94	25.40	
IC-D03-24	30.48	27.94	
IC-D03-28	35.56	33.02	
IC-D03-32	40.64	38.10	

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm


SCALE 1:1

DATE

SIZE A4

P PROJECTION

X. ± 0.25
 X. ± 0.20
 .XX ± 0.10
 .XXX ±
 ANG ±



ORDER INFORMATION

IC-D03-xx-LF
 SERIES | LEADFREE
 06~32WAY
 SPACING 7.62mm
 DIP 180°

DESCRIPTION: