

1. Housing:

1.1 Material: PBT + glass fiber

1.2 Color: black

2. Terminal:

2.1 Material: Phosphorus copper

2.2 Surface treatment/finish: Nickel plated (100u"min)

2.3 Instant thrust: 0.5kg per pin

3. Electrical reference:

3.1 Current rating: 1A

3.2 Dielectric withstanding voltage: AC 1000V/5S

3.3 Insulator resistance: 1000 Megohms 500V DC

3.4 Operating temperature: 55°C ~ +105°C

NO.	A	B
24	30.48	27.94
28	35.56	33.02
32	40.64	38.10
40	50.80	48.26
42	53.34	50.80
48	60.96	58.42

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS


UNIT/ mm SCALE 1:1

DATE

SIZE A4

X. ±
.X ±
.XX ±
.XXX ±
ANG ±

P PROJECTION



ORDER INFORMATION

IC-D06-xx-LF
SERIES LEADFREE
24~48WAY
SPACING 15.24mm
DIP 180°

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: IC SOCKET 2.54MM SERIES