



ASSEMBLY LAYOUT

MATERIALS

HOUSING: LCP (UL 94V-0), BEIGE
 TERMINAL: COPPER ALLOY, TIN PLATING

SPECIFICATION

CURRENT RATING: 2 AMP MAX
 DIELECTRIC WITHSTANDING: 1500V AC FOR ONE MINUTE
 CONTACT RESISTANCE: 20m OHMS MAX
 INSULATION RESISTANCE: 800M OHMS MIN AT DC 500V
 OPERATION TEMPERATURE: -40°C~+85°C
 APPLICABLE: AWG #24

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X. ± 0.40
 .X ± 0.30
 .XX ± 0.20
 .XXX ± 0.10
 ANG ±

PJECTION

照片框

ORDER INFORMATION

IDT040-VI5524-02-LF

SERIES | | | LEADFREE
 | | | 02 WAY
 | | | 24 AWG
 | | | HIGH 5.5mm
 | | | IDC
 | | | 180°SMT

DESCRIPTION: POKE HOME, 4.00mm PITCH, PCB MOUNT, SMT, FEMALE (AWG #24)

煜倫股份有限公司

www.morethanall.com