


SHELL SIZE	A±0.10	B±0.15	C±0.15	D±0.20
6	10.82	5.08	6.35	11.52
8	13.36	7.62	8.89	14.06
10	15.90	10.16	11.43	16.6
12	18.44	12.7	13.97	19.14
14	20.98	15.24	16.51	21.68
16	23.52	17.78	19.05	24.22
18	26.06	20.32	21.59	26.76
20	28.60	22.86	24.13	29.3
22	31.14	25.4	26.67	31.84
24	33.68	27.94	29.21	34.38
26	36.22	30.48	31.75	36.92
28	38.76	33.02	34.29	39.46
30	41.30	35.56	36.83	42.00
32	43.84	38.1	39.37	44.54
34	46.38	40.64	41.91	47.08
36	48.92	43.18	44.45	49.62
40	54.00	48.26	49.53	54.7
44	59.08	53.34	54.61	59.78
50	66.70	60.96	62.23	67.4
60	79.4	73.66	74.93	80.1
64	84.48	78.74	80.01	85.18

MATERIAL
 INSULATOR:PBT&GLASS-FIBER REINFORCED UL94V-0
 CONTACT:BRASS OR PHOSPH BRONZE GOLD FLASH OVER NICKEL
 SPECIFICATION:
 CONTACT SPACING: 2.54mm GRID
 CURRENT RATING: 1 AMP DC
 CONTACT RESISTANCE: 30 MILLI OHMS MAX AT 6V DC 0.3A
 INSULATION RESISTANCE: 1000M OHMS MIN AT 500V DC
 OPERATING TEMPERATUE: -55°-+105°



MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

RoHS Compliant

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

TOLERANCES ARE

X. ±
 .X ±
 .XX ±
 .XXX ±
 ANG ±

PPOJECTION

照片框

ORDER INFORMATION

IP01-C2L-xx-LF

SERIES | LEADFREE
 | 06-64WAY
 | LOCK
 | TWO TYPE

DESCRIPTION: