



| P1 | COLOR | P2 | P1 | COLOR | P2 | P1 | COLOR | P2 | WIRE LENGTH | NO | MATERIAL | NO | MATERIAL |
|----|-------|----|----|-------|----|----|-------|----|-------------|---------------------------|---|-----|---|
| 1 | GRAY | 1 | | | | | | | 650 ± 5 mm | 1. | UL 2651 26AWG TOP-COATED TINNED COPPER PITCH:2.54mm | 16C | VW-1 CSA 105°C 300V JUMP CABLE COLOR:GRAY |
| 2 | GRAY | 2 | | | | | | 2. | | SEMI-STRIPPED 5.0 ± 1.0mm | 4. | | |
| 3 | GRAY | 3 | | | | | | 3. | | | 5. | | |
| | | | | | | | | | CUT LENGTH | | | | |
| 14 | GRAY | 14 | | | | | | | | | | | |
| 15 | GRAY | 15 | | | | | | | | | | | |
| 16 | GRAY | 16 | | | | | | | | | | | |

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X. ±

.X ±

.XX ±

.XXX ±

ANG ±

PJECTION

照片框

ORDER INFORMATION

JC-16-650-LF
SERIES | LEADFREE
LONG 650mm
16 WAY

DESCRIPTION: