



■ MATERIAL

INSULATOR: PA-9T GLASS FIBER (UL94V-0). Black
 CONTACT: PHOSPHOR BRONZE OR BRASS.
 PLATING: GOLD OVER NICKEL.

■ SPECIFICATION

CURRENT RATING: 3 AMP.
 INSULATION RESISTANCE: 5000 MEGOHMS MIN AT 500 VDC.
 CONTACT RESISTANCE: 20 MILLIOHMS MAX.
 VOLTAGE : 500V FOR ONE MINUTE.

■ ENVIRONMENTAL

TEMPERATURE RANGE: -40°C TO +105°C.

Circuit	Dimension			Circuit	Dimension		
	A	B	C		A	B	C
10	15.84	24.06	27.40	64	122.76	130.98	134.32
12	19.80	28.02	31.36	70	134.64	142.86	146.20
16	27.72	35.94	39.28	72	138.60	146.82	150.16
20	35.64	43.86	47.20				
24	43.56	51.78	55.12				
26	47.52	55.74	59.08				
28	51.48	59.70	63.04				
30	55.44	63.66	67.00				
32	59.40	67.62	70.96				
36	67.32	75.54	78.88				
40	75.24	83.46	86.80				
44	83.16	91.38	94.72				
46	87.12	95.34	98.68				
50	95.04	103.26	106.60				
56	106.92	115.14	118.48				
60	114.84	123.06	126.40				
62	118.80	127.02	130.36				

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

0-10 ±0.2

30-100 ±0.4

OVER 300 ±0.6

PPOJECTION

照片框

ORDER INFORMATION

KE-DXEN9T-xx-LF
 SERIES | PA 9T | LEADFREE
 | | 10~72 WAY
 | | NON EAR
 | | DIP 180°

DESCRIPTION: 3.96 PITCH WITH OUT MOUNTING EAR