



CABLE	DIM
BLUE(SHORT)	85±5
BROWN(SHORT)	85±5
BLUE(LONG)	220±10
BROWN(LONG)	230±10

Note: the above wire sizes do not include conn at both ends.

NOTES:

1. ALL DIMENSIONS ARE "mm".
2. THE PRODUCT MUST BE COMPLY WITH THE DIRECTIVE OF ROHS.

ELECTRICAL TESTING:

1. 100% OPEN/SHORT TEST
2. CONTACT RESISTANCE: 5mΩ
3. INSULATION RESISTANCE: 5MΩ Min

NO.	ITEM.	DESCRIPTION	Q'TY	UL/CSA No.
1	WIRE:	UL1007 #22 BLUE	1PCS	E108485
2	WIRE:	UL1007 #22 BROWN	1PCS	E108485
3	WIRE:	UL1007 #22 BLUE	1PCS	E108485
4	WIRE:	UL1007 #22 BROWN	1PCS	E108485
5	HOUSING:	09-50-8031 (MOLEX)	2PCS	
6	TERMINAL:	08-50-0106 (MOLEX)	4PCS	
7	TERMINAL:	Q250-FT8VF-14	2PCS	
8				
9				

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X, ±  
.X ±  
.XX ±  
.XXX ±  
ANG ±

PJECTION

照片框

ORDER INFORMATION

KKQTX21-0368VF22MX-F23C-LF

SERIES

03 WAY TO 6.3X0.8

22 AWG

VINYL FULL

LEADFREE  
230mm  
FEMALE TO FEMALE

DESCRIPTION: