

NOTES:

1. ALL DIMENSIONS ARE "mm".
2. THE PRODUCT MUST BE COMPLY WITH THE DIRECTIVE OF ROHS.

ELECTRICAL TESTING:

1. 100% OPEN/SHORT TEST
2. CONTACT RESISTANCE: 5mΩ
3. INSULATION RESISTANCE: 5MΩ Min

NO.	ITEM.	DESCRIPTION	Q'TY
1	WIRE:	UL1007 #18 BLACK	1PCS
2	WIRE:	UL1007 #18 GREEN	1PCS
3	WIRE:	UL1007 #18 BLUE	1PCS
4	WIRE:	UL1007 #18 ORANGE	1PCS
5	WIRE:	UL1007 #18 BROWN	1PCS
6	WIRE:	UL1007 #18 WHITE	1PCS
7	WIRE:	UL1007 #18 RED	1PCS
8	HOUSING:	KK-H-08	1PCS
9	TERMINAL:	KK-T-18	7PCS
10	Waterproof label		1PCS
11	CABLE TIE:	NATURE COLOR 2.5*100mm	5PCS

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS


UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X. ±
.X ±
.XX ±
.XXX ±
ANG ±

PJECTION



ORDER INFORMATION

KKX1-080018CT5-F35N75-LF

SERIES | 18 AWG | 08 WAY | 908.1mm LEADFREE
FEMALE
CABLE TIE x5

DESCRIPTION: CABLE ASS"Y

煜倫股份有限公司

www.morethanall.com