

MATERIAL

Contact Pin : Brass

Insulator: NY6T UL94-V0

SPECIFICATION

Current Rate : 1 AMP

Insulation Resistance : 5000MΩMin. at DC 500V

Contact Resistance : 20mΩMax. at DC 100mA

Dielectric Voltage : AC 500V for one minute

Operation Temperature : -40°C to + 105°C

POLES	DIM D	DIM E	POLES	DIM D	DIM E
			21	40.00	41.75
2	2.00	3.75	22	42.00	43.75
3	4.00	5.75	23	44.00	45.75
4	6.00	7.75	24	46.00	47.75
5	8.00	9.75	25	48.00	49.75
6	10.00	11.75	26	50.00	51.75
7	12.00	13.75	27	52.00	53.75
8	14.00	15.75	28	54.00	55.75
9	16.00	17.75	29	56.00	57.75
10	18.00	19.75	30	58.00	59.75
11	20.00	21.75	31	60.00	61.75
12	22.00	23.75	32	62.00	63.75
13	24.00	25.75	33	64.00	65.75
14	26.00	27.75	34	66.00	67.75
15	28.00	29.75	35	68.00	69.75
16	30.00	31.75	36	70.00	71.75
17	32.00	33.75	37	72.00	73.75
18	34.00	35.75	38	74.00	75.75
19	36.00	37.75	39	76.00	77.75
20	38.00	39.75	40	78.00	80.00

RoHS Compliant

TOLERANCES ARE



煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE


SIZE A4

X, ±
.X ± 0.30
.XX ± 0.20
.XXX ±
ANG ± 3°

PJECTION

照片框

ORDER INFORMATION



DESCRIPTION: PIN HEADER 2.00*2.00mm STRAIGHT TYPE, DUAL ROWS