



Technical specifications:		Materials:	
Coupling:	Threaded coupling	Shell material:	Brass nickel plated
Termination:	Dip solder	Contact material:	Brass Gold plated
Coding:	A	Insert material:	PA66+GF UL94 black
Pollution degree:	3	Sealing:	NBR
Temperature range:	-40°C ~ +80°C		
Degree of protection:	IP67		
Mating cycles:	≥500		
Rated voltage:	60V AC/DC		
Rated current:	4A		
Contact resistance:	≤5 mΩ		
Insulation resistance:	≥100 MΩ		
All materials are RoHS compliant			

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X. ± 0.50  
.X ± 0.38  
.XX ± 0.25  
.XXX ± 0.10  
ANG ± 3°

照片框

ORDER INFORMATION

M12-PRPBNOLP-05-LF  
SERIES | | | | | LEADFREE  
MALE | | | | | 05 WAY  
DIP 90° | | | | | POST  
PANEL BACK | | | | | LOCK  
NUT | | | | | RING

DESCRIPTION: M12 Angled Male back mount socket 5 core