



TABLE A

ASSEMBLY

BLACK NICKEL

NICKEL 60u" ~ 100u"

1. MATERIAL :

- 1-1. HOUSING : PBT UL94V-0;COLOR: BLACK
- 1-2. CONTACT : BRASS
- 1-3. NUT : BRASS
- 1-4. O-RING :EPDM; COLOR : BLACK
- 1-5. Epoxy Base :EF400A&EF400B.COLOR:BLACK

2. FINISH :

- 2-1. CONTACT A : 10 MICRO INCHES MIN. GOLD PLATED
UNDER PLATE : NICKEL
- 2-2. NUT : NICKEL PLATED 60u" ~ 100u" OVER ALL

3. ELECTRICAL SPECIFICATION :

- 3-1. Rated current : 5A
- 3-2. Voltage :125V
- 3-3. Water proof: IPX7

4. Environmental :

- 4-1. Operation Temperature : -40 °C~85°C

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES
煜倫股份有限公司

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PJECTION

X. ±
.X ±
.XX ±
.XXX ±
ANG ±



ORDER INFORMATION

M12-PS-08-LF
SERIES | LEADFREE
| 08 WAY
| SOLDER
MALE

DESCRIPTION: 防水頭 8 PIN (M)

www.morethanall.com