



NUT

RECOMMEND PANEL CUT-OUT

1. MATERIAL :
 - 1-1. HOUSING : PBT UL94V-0 ; COLOR : BLACK
 - 1-2. CONTACT : BRASS
 - 1-3. NUT : BRASS
 - 1-4. SHELL : BRASS
 - 1-5. O-RING : EPDM
 - 1-6. X-SHELL : Zn ALLOY
2. FINISH :
 - 2-1. CONTACT : 10 MICRO INCHES MIN. GOLD PLATE^D
UNDER PLATE : NICKEL
 - 2-2. NUT : NICKEL PLATED
 - 2-3. SHELL : NICKEL PLATED
 - 2-4. X-SHELL : NICKEL PLATED
3. ELECTRICAL SPECIFICATION :
 - 3-1. Rated current : 0.5A
 - 3-2. Rated Voltage : 48V
 - 3-3. Water proof: IP67
4. Environmental :
 - 4-1. Operation Temperature : -40°C~85°C
5. Applicable cable 26AWG-24AWG

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X, ±
.X ± 0.20
.XX ± 0.10
.XXX ± 0.05
ANG ± 1°

P PROJECTION

照片框

ORDER INFORMATION

M12-PSPANO-08X-LF
SERIES | | | | LEADFREE
MALE | | | | 08WAY X-CODE
RING
NUT
PANEL FRONT
SOLDER

DESCRIPTION: 防水頭 M12 X-Code 8PIN(M) 後鎖 PG9 焊線式(IEC TYPE)