



1. MATERIAL :
- 1-1. NY-WPXXX :
 - a. HOUSING : PBT UL94V-0 ; COLOR : BLACK.
 - b. CONTACT : BRASS
 - c. NUT : ALUMINUM ALLOY
 - d. SHELL : ALUMINUM ALLOY
 - e. O-RING : EPDM ; COLOR : BLACK
 - f. Epoxy Base : EF400A&EF400B. COLOR : BLACK.
 - 1-2. Main Body : ALUMINUM ALLOY
 - 1-3. Gland : SILICONE COLOR : BLACK.
 - 1-4. Gland Cage : POM ; COLOR : BLACK.
 - 1-5. Gland Nut : ALUMINUM ALLOY
2. FINISH :
- 2-1. NY-WPXXX :
 - a. CONTACT : GOLD FLASH MICRO INCHES MIN.
UNDER PLATE : NICKEL.
 - b. NUT : SATIN Ni PLATED.
 - c. SHELL : SATIN Ni PLATED.
 - 2-2. Main Body : SATIN Ni PLATED.
 - 2-3. Gland Nut : SATIN Ni PLATED.
3. ELECTRICAL SPECIFICATION :
- 3-1. Rated current : 5A
 - 3-2. Rated Voltage : 125V
 - 3-3. Water proof : IPX7
4. Environmental :
- 4-1. Operation Temperature : -20 ℃~85℃

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X. ± 0.30

.X ± 0.20

.XX ± 0.10

.XXX ± 0.05

ANG ± 1°

PPOJECTION

照片框

ORDER INFORMATION

M12-SA-08-LF
SERIES | LEADFREE
08 WAY
ASSEMBLY
FEMALE

DESCRIPTION: M12 8PINK) A-coded Assembly type