



1. MATERIAL
 INSULATION: THERMOPLASTIC UL94V-0
 COLOR: BLACK.
 CONTACT: BRASS
 SHELL: BRASS
2. PLATING
 CONTACT: GOLD 10 μ "
 Shell: NICKEL 100 μ "
3. SPECIFICATION
 CURRENT: 2 A.
 OPERATING TEMPERATURE: -20° C TO 105° C.
 INSULATION RESISTANCE: 1000 MEGAOHMS MIN.
 DIELECTRIC STRENGTH: 500V AC MIN.

TYPE A

Item	Description	Material	UL File No.
1	Insulation	1403G6	E130155
2	Pin	JIS H3250 C3604 BD	
3	Shell	C3604	
4	O-Ring	NBR	

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X. \pm
 .X \pm
 .XX \pm
 .XXX \pm
 ANG \pm

P PROJECTION



ORDER INFORMATION

M12-SS-02-LF
 SERIES | LEADFREE
 | 02 WAY
 | SOLDER
 | FEMALE

DESCRIPTION: 防水頭 2P(F) 線端