



NUT

RECOMMEND PANEL CUT-OUT

TABLE A

M12-SSPBNO9-08X	ø10.3	ø9.0
M12-SSPBNO8-08X	ø9.3	ø8.0
M12-SSPBNO7-08X	ø8.5	ø7.2
PART No.	D1	D2

- MATERIAL :
 - HOUSING : PA66 ; COLOR : BLACK
 - CONTACT : BRASS
 - NUT : BRASS
 - SHELL : BRASS
 - O-RING : SILICONE UL94V-0.
 - X-SHELL : Zn ALLOY
 - BACK SHELL : BRASS
- FINISH :
 - CONTACT : 10 MICRO INCHES MIN. GOLD PLATED
UNDER PLATE : NICKEL
 - NUT : NICKEL PLATED
 - SHELL : NICKEL PLATED
 - X-SHELL : NICKEL PLATED
 - BACK SHELL : NICKEL PLATED
- ELECTRICAL SPECIFICATION :
 - Rated current : 0.5A
 - Rated Voltage : 48V
 - Water proof: IP67
- Environmental :
 - Operation Temperature : -40°C~85°C

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1:1

DATE

SIZE A4

X, ±
.X ± 0.20
.XX ± 0.10
.XXX ± 0.05
ANG ± 1°

PJECTION

照片框

ORDER INFORMATION

M12-SSPBNOx-08X-LF
SERIES | | | | | LEADFREE
| | | | | 08WAY X CODE
| | | | | 9:9.00
| | | | | 8:8.00
| | | | | 7:7.00
FEMALE | | | | | METAL SLEEVE
SOLDER | | | | | RING
PANEL BACK | | | | | NUT

DESCRIPTION: 防水頭 M12 8PIN X-Code (F) 前鎖PG9 焊線式(無溝槽+接地銅管+後銅管)