



P1	WIRE COLOR 線材顏色	P2
1	WHITE/ORANGE(白/橘)	1
3	ORANGE(橘)	2
2	WHITE/GREEN(白/綠)	3
N/A	BLUE(藍)	4
N/A	WHITE/BLUE(白/藍)	5
4	GREEN(綠)	6
N/A	WHITE/BROWN(白/棕)	7
N/A	BROWN(棕)	8
Shield	Drain	Shield

MATERIALS:

- 1.PLASTIC HOUSING : ENGINEERING PLASTIC
FLAMMABILITY RATING UL 94V-0. COLOR GREEN
- 2.CONTACTS : COPPER ALLOY WITH GOLD PLATING OVER NICKEL IN CONTACT
- 3.GROUNDING METAL RING : BRASS WITH NICKEL PLATED
- 4.COULPING NUT : M12*1 BRASS WITH NICKEL PLATED
- 5.OVER MOLD : PVC BLACK COLOR

Current Rating: 4A(2 to 4PIN)
Rated voltage: 250V AC/DC(2 to 4PIN)
Insulation Resistance: 100 Megaohm min.
Degree of protection : IP67

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X. ± 0.38
.X ± 0.25
.XX ± 0.10
.XXX ± 0.05
ANG ± 3°

PPOJECTION

照片框

ORDER INFORMATION

M12RJ-04DR0826C5E-Mxxx-LF

SERIES

04P D CODE 90° TO 8P8C

CAT.5E

26 AWG

LEADFREE
1M:1000mm
2M:2000mm
3M:3000mm
MALE TO MALE

DESCRIPTION: M12-4P(D-綠-S-90) to RJ45 Plug for CAT5E Cable