



***CONSTRUCTION:

1.CABLE: * NO UL (4C/22#) OD:5.2mm BLACK PVC JACKET.

***CONNECTORS:

2.M12-4PIN: * M12-4PIN FEMALE SOLDER TYPE.
 * PIN: BRASS WITH GOLD PLATED.
 * INSULATOR: BLACK NYLON 66 UL 94V-0 RATED.
 * SHELL: BRASS WITH NICKEL PLATED.
 * O-RING: SILICONE RUBBER RED COLOR.
 * MOLDED: PVC 30P BLACK.

3.TEST: * CT: 2 Ohm. IS: 5M Ohm.
 * RATE CURRENT: 4A RATE VOLTAGE: MAX.250V

4.PACKING: * PACK EACH CABLE IN A POLY BAG.

5.MATERIAL: * MATERIAL WITH RoHS GRADE.

PIN OUT

M12-4F		M12-4F
1	BROWN	1
2	WHITE	2
3	BLUE	3
4	BLACK	4

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

RoHS Compliant

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

TOLERANCES ARE

X, ±
 .X ±
 .XX ±
 .XXX ±
 ANG ±

PPOJECTION

照片框

ORDER INFORMATION

M12X2-040422BK-F1M-LF

SERIES
 LEADFREE
 1 METER
 MALE TO FEMALE
 BLACK
 22AWG
 04 TO 04 PIN

DESCRIPTION: M12-4PIN FEMALE TO FEMALE