



Scale 2:1

Specifications:

1. Poles: 8.
2. Rated Voltage: 48V.
3. Rated Current: 0.5A.
4. Contact resistance:<15mΩ.
5. Insulation resistance:>100MΩ.
6. protection:IP68,Mated.
7. Temperature range:-40°C~85°C.

Terminal	Wire Harness		Terminal
Shield	Drain	地線	Shield
8	Blue	藍	8
7	White	白	7
6	Brown	棕	6
5	White	白	5
4	Green	綠	4
3	White	白	3
2	Orange	橙	2
1	White	白	1
P1	Wire Color		P2

Note:

1. Metal Housing:Zinc Alloy,Nickel Plated.
2. Nut:Brass · Nickel Plated.
3. Contact:Brass,Gold Over Nickel Plated.
4. Plastic Housing:PBT · Green.
5. Insert Molding:PVC,Black.
6. Cable:S/FTP 26AWG*4P,LSZH Jacket.OD=φ5.8±0.3mm.

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X. ± 0.50

.X ± 0.38

.XX ± 0.25

.XXX ± 0.10

ANG ± 3°

PJECTION

照片框

ORDER INFORMATION

M12X2-08X08X26BK-M50C-LF

SERIES

LEADFREE
500mm
MALE TO MALE
BLACK
26 AWG
08 X CODE TO 08 X CODE

DESCRIPTION: 纜-8P-雙頭(39cm)